

UL PRODUCT CATEGORY

Clean-agent Extinguishing System Units

See General Information for Clean-agent Extinguishing System Units

EVERSAFE EXTINGUISHER SDN BHD

EX15573

LOT 878

JALAN SUBANG 9

TAMAN PERINDUSTRIAN SUBANG

47500 SUBANG JAYA, SELANGOR SELANGOR DARUL EHSAN MALAYSIA

ENGINEERED UNITS, NAF S 125 (HFC-125 with limonene additive, 0.15% by weight) Clean Agent Extinguishing System Units, stored pressure type, having nominal charging capacities of 5, 13.4, 26.8, 40.2, 67.5, 75, 100 and 120 L. The units are super pressurized to 42 bar at 21°C with operating temperatures of 0 °C to +50 °C. The units are designed for total flooding protection against Class A surface burning, Class B flammable liquid and Class C fires occurring within an enclosure.

A description of these extinguishing system units and the design and installation limitations are contained in the Listee's installation manual P/N SHIM125227 Rev. 02 dated December 2014 and design manual P/N SHDM125 dated February 2014. These installations require the use of the Listee's flow calculation software NAF S 125 Flow Calculation Program Version SHT 4.00 dated July 2014 floppy disc or CD accessed through Safety Hi-Tech, User's Manual SHT 4.00. Copies are available from the above Listee.

AGENT STORAGE CONTAINER ASSEMBLY

Weight of Agent (kg)	Part No.
2.5-4.0	SH70025410
6.5-12.5	SH70025409
13.0-24.5	SH70025408
19.5-37.0	SH70025407
32.5-62.0	SH70025412
36.0-70.5	SH70025405
48.5-93.0	SH70025404
58.0-111.5	SH70025403

ENGINEERED UNITS, NAF S 125 (HFC-125 with limonene additive, 0.15% by weight) Clean Agent Extinguishing System Units, stored pressure type, having nominal charging capacities of 26.8, 40.2, 75, 120, 142, 175 and 240 L. The units are super pressurized to 25 bar at 21°C with operating temperatures of 0 °C to +50 °C. The units are designed for total flooding protection against Class A surface burning, Class B flammable liquid and Class C fires occurring within an enclosure.

A description of these extinguishing system units and the design and installation limitations are contained in the Listee's installation manual P/N SHIM125227 Rev. 02 dated December 2014 and design manual P/N SHDM125 dated February 2014. These installations require the use of the Listee's flow calculation software NAF S 125 Flow Calculation Program Version SHT 4.00 dated July 2014 floppy disc or CD accessed through Safety Hi-Tech, User's Manual SHT 4.00. Copies are available from the above Listee.

AGENT STORAGE CONTAINER ASSEMBLY

Weight of Agent (kg)	Part No.
13.0-24.5	SH72525408
19.5-37.0	SH72525407
36.0-70.5	SH72525405
58.0-111.5	SH72525403
68.5-132.0	SH70025413
84.5-162.5	SH70025414
115.5-223.0	SH70025415

ENGINEERED UNITS, NAF S 227 (HFC-227ea with limonene additive, 0.15% by weight) Clean Agent Extinguishing Systems Units, stored pressure types, having nominal capacities of 5, 13.4, 26.8, 40.2, 67.5, 75, 100 and 120L. The units are super pressurized to 42 bar at 21°C with operating temperatures of 0 °C to + 50 °C. The units are designed for total flooding protection against Class A surface burning, Class B flammable liquid and Class C fires occurring within an enclosure.

A description of these extinguishing system units and the design and installation limitations are contained in the Listee's installation manual P/N SHIM125227 Rev. 02 dated December 2014 and design manual P/N SHDM227 dated February 2014. These installations require the use of the Listee's flow calculation software NAF S 227® Flow Calculation Software Version SHT 4.00 dated July 2014 floppy disc or CD accessed through Safety Hi-Tech, User's Manual SHT 4.00. Copies are available from the above Listee.

AGENT STORAGE CONTAINER ASSEMBLY

Weight of Agent (kg)	Part No.
2.5-5.5	SH70027410
6.5-15.0	SH70027409
13.0-30.5	SH70027408
19.5-46.0	SH70027407
32.5-77.0	SH70027412
36.5-86.0	SH70027405
48.5-115.0	SH70027404
58.0-138.0	SH70027403

ENGINEERED UNITS, NAF S 227 (HFC-227ea with limonene additive, 0.15% by weight) Clean Agent Extinguishing System Units, stored pressure type, having nominal capacities of 26.8, 40.2, 75, 120, 142, 175 and 240 liters. The units are super pressurized to 25 bar at 21°C with operating temperature of 0 °C to + 50 °C. The units are designed for total flooding protection against Class A surface burning, Class B flammable liquid and Class C fires occurring within an enclosure.

A description of these extinguishing system units and the design and installation limitations are contained in the Listee's installation manual P/N SHIM125227 Rev. 02 dated December 2014 and design manual P/N SHDM227 dated February 2014. These installations require the use of the Listee's flow calculation software NAF S 227® Flow Calculation Software Version SHT 4.00 dated July 2014 floppy disc or CD accessed through Safety Hi-Tech, User's Manual SHT 4.00. Copies are available from the above Listee.

AGENT STORAGE CONTAINER ASSEMBLY

Weight of Agent (kg)	Part No.
13.0-30.5	SH72527408
19.0-46.0	SH72527407
36.5-86.0	SH72527405
58.0-138.0	SH72527403
68.5-159.0	SH70027413
84.5-196.0	SH70027414
115.5-268.5	SH70027415

ENGINEERED UNIT, EVERSAFE IG-55 at 2900 or 4350 psi (200 or 300 bar) IG-55 (Ar & N2) Clean Agent Extinguishing System Units, stored pressure type, having nominal charging capacities as identified below. The units are pressurized to 200 or 300 bar with operating temperatures of -4°F (-20°C) to 122°F (50°C). The units are designed for total-flooding protection against Class A surface burning, Class B flammable liquid, and Class C fires occurring within an enclosure.

A description of these extinguishing system units and the design and installation limitations are contained in the Listee's Installation manual, P/N I.IG-55.Rv.01, Design Manual, P/N D.IG-55.Rv.01, Components Manual P/N C.IG-55.Rv.01, and Maintenance Manual P/N M.IG-55.Rv.01. These installations require the use of the Listee's flow calculation software IG55-Calculation program, Version 7.3. Copies are available from the above Listee.

AGENT STORAGE CONTAINER ASSEMBLY

Nominal Capacity (L)	Part No.
2 - 200 bar	55M2UFV-1
2 - 200 bar	55M2UFV-2
2 - 200 bar	55M2UFV-3
2.7 - 200 bar	55M2UFJ-1
2.7 - 200 bar	55M2UFJ-2

2.7 - 200 bar	55M2UFJ-3
2.7 - 200 bar	55M2UFV-4
2.7 - 200 bar	55M2UFV-5
2.7 - 200 bar	55M2UFV-6
4.7 - 200 bar	55M4UFJ-1
4.7 - 200 bar	55M4UFJ-2
4.7 - 200 bar	55M4UFJ-3
4.7 - 200 bar	55M4UFJ-4
4.7 - 200 bar	55M4UFJ-5
4.7 - 200 bar	55M4UFJ-6
4.7 - 200 bar	55M4UFV-1
4.7 - 200 bar	55M4UFV-2
4.7 - 200 bar	55M4UFV-3
4.7 - 200 bar	55M4UFV-4
4.7 - 200 bar	55M4UFV-5
4.7 - 200 bar	55M4UFV-6
6.7 - 200 bar	55M6UFJ-1
6.7 - 200 bar	55M6UFJ-2
6.7 - 200 bar	55M6UFJ-3
6.7 - 200 bar	55M6UFV-1
6.7 - 200 bar	55M6UFV-2
6.7 - 200 bar	55M6UFV-3
13.4 - 200 bar	55M13UFV-1
13.4 - 200 bar	55M13UFV-2
13.4 - 200 bar	55M13UFV-3
13.4 - 200 bar	55M13UFB-1
13.4 - 200 bar	55M13UFB-2
13.4 - 200 bar	55M13UFB-3
13.4 - 200 bar	55M13UFJ-1
13.4 - 200 bar	55M13UFJ-2
13.4 - 200 bar	55M13UFJ-3
13.4 - 200 bar	55M13UFV-4
13.4 - 200 bar	55M13UFV-5
13.4 - 200 bar	55M13UFV-6

26.8 - 200 bar	55M26UFB-1
26.8 - 200 bar	55M26UFB-2
26.8 - 200 bar	55M26UFB-3
26.8 - 200 bar	55M26UFJ-1
26.8 - 200 bar	55M26UFJ-2
26.8 - 200 bar	55M26UFJ-3
26.8 - 200 bar	55M26UFJ-4
26.8 - 200 bar	55M26UFJ-5
26.8 - 200 bar	55M26UFJ-6
26.8 - 200 bar	55M26UFV-1
26.8 - 200 bar	55M26UFV-2
26.8 - 200 bar	55M26UFV-3
26.8 - 200 bar	55M26UFV-4
26.8 - 200 bar	55M26UFV-5
26.8 - 200 bar	55M26UFV-6
26.8 - 200/300 bar	55M26UFV-7
26.8 - 200/300 bar	55M26UFV-8
26.8 - 200/300 bar	55M26UFV-9
26.8 - 200/300 bar	55M26UFV-10
26.8 - 200/300 bar	55M26UFV-14
26.8 - 200 bar	55M26UFV-11
26.8 - 200 bar	55M26UFV-12
26.8 - 200 bar	55M26UFV-13
40 - 200 bar	55M40UFJ-1
40 - 200 bar	55M40UFJ-2
40 - 200 bar	55M40UFJ-3
40 - 200 bar	55M40UFJ-4
40 - 200 bar	55M40UFJ-5
40 - 200 bar	55M40UFJ-6
40 - 200 bar	55M40UFN-1
40 - 200 bar	55M40UFN-2
40 - 200 bar	55M40UFN-3
40 - 200/300 bar	55M40UFN-4

40 - 200/300 bar	55M40UFN-5
40 - 200/300 bar	55M40UFN-6
40 - 200/300 bar	55M40UFN-7
40 - 200/300 bar	55M40UFN-8
40 - 200 bar	55M40UFV-1
40.2 - 200 bar	55M40UFV-2
40.2 - 200 bar	55M40UFV-3
40.2 - 200 bar	55M40UFV-4
40.2 - 200 bar	55M40UFV-5
40.2 - 200 bar	55M40UFV-6
40.2 - 200/300 bar	55M40UFV-7
40.2 - 200/300 bar	55M40UFV-8
40.2 - 200/300 bar	55M40UFV-9
40.2 - 200/300 bar	55M40UFV-10
40.2 - 200/300 bar	55M40UFV-14
40.2 - 200 bar	55M40UFV-11
40.2 - 200 bar	55M40UFV-12
40.2 - 200 bar	55M40UFV-13
67.5 - 200 bar	55M67UFB-1
67.5 - 200 bar	55M67UFB-2
67.5 - 200 bar	55M67UFB-3
67.5 - 200 bar	55M67UFJ-1
67.5 - 200 bar	55M67UFJ-2
67.5 - 200 bar	55M67UFJ-3
67.5 - 200 bar	55M67UFR-1
67.5 - 200 bar	55M67UFR-2
67.5 - 200 bar	55M67UFR-3
67.5 - 200/300 bar	55M67UFV-1
67.5 - 200/300 bar	55M67UFV-2
67.5 - 200/300 bar	55M67UFV-3
67.5 - 200/300 bar	55M67UFV-4
67.5 - 200/300 bar	55M67UFV-11
68 - 200 bar	55M67UFV-5
68 - 200 bar	55M67UFV-6

68 - 200 bar	55M67UFV-7
67.5 - 200 bar	55M67UFV-8
67.5 - 200 bar	55M67UFV-9
67.5 - 200 bar	55M67UFV-10
80 - 200 bar	55M80UFJ-1
80 - 200 bar	55M80UFJ-2
80 - 200 bar	55M80UFJ-3
80 - 200 bar	55M80UFC-1
80 - 200 bar	55M80UFC-2
80 - 200 bar	55M80UFC-3
80 - 200 bar	55M80UFR-1
80 - 200 bar	55M80UFR-2
80 - 200 bar	55M80UFR-3
80 - 200 bar	55M80UFV-1
80 - 200 bar	55M80UFV-2
80 - 200 bar	55M80UFV-3
80 - 200 bar	55M80UFB-1
80 - 200 bar	55M80UFB-2
80 - 200 bar	55M80UFB-3
80 - 200/300 bar	55M80UFC-4
80 - 200/300 bar	55M80UFC-5
80 - 200/300 bar	55M80UFC-6
80 - 200/300 bar	55M80UFC-7
80 - 200/300 bar	55M80UFC-8
80 - 200/300 bar	55M80UFV-4
80 - 200/300 bar	55M80UFV-5
80 - 200/300 bar	55M80UFV-6
80 - 200/300 bar	55M80UFV-7
80 - 200/300 bar	55M80UFV-11
80 - 200 bar	55M80UFV-8
80 - 200 bar	55M80UFV-9
80 - 200 bar	55M80UFV-10
100 - 200 bar	55M100UFR-1

100 - 200 bar	55M100UFR-2
100 - 200 bar	55M100UFR-3
100 - 200 bar	55M100UFV-1
100 - 200 bar	55M100UFV-2
100 - 200 bar	55M100UFV-3
100 - 200 bar	55M100UFV-4
100 - 200 bar	55M100UFV-5
100 - 200 bar	55M100UFV-6
120 - 200 bar	55M120UFR-1
120 - 200 bar	55M120UFR-2
120 - 200 bar	55M120UFR-3
120 - 200 bar	55M120UFV-1
120 - 200 bar	55M120UFV-2
120 - 200 bar	55M120UFV-3
120 - 200 bar	55M120UFV-4
120 - 200 bar	55M120UFV-5
120 - 200 bar	55M120UFV-6
140 - 200 bar	55M140UFC-1
140 - 200 bar	55M140UFC-2
140 - 200 bar	55M140UFC-3
140 - 200 bar	55M140UFR-1
140 - 200 bar	55M140UFR-2
140 - 200 bar	55M140UFR-3
140 - 200 bar	55M140UFV-1
140 - 200 bar	55M140UFV-2
140 - 200 bar	55M140UFV-3
140 - 200/300 bar	55M140UFC-4
140 - 200/300 bar	55M140UFC-5
140 - 200/300 bar	55M140UFC-6
140 - 200/300 bar	55M140UFC-7
140 - 200/300 bar	55M140UFC-8
140 - 200/300 bar	55M140UFV-4
140 - 200/300 bar	55M140UFV-5
140 - 200/300 bar	55M140UFV-6

140 - 200/300 bar	55M140UFV-7
140 - 200/300 bar	55M140UFV-11
140 - 200 bar	55M140UFV-8
140 - 200 bar	55M140UFV-9
140 - 200 bar	55M140UFV-10
150 - 200 bar	55M150UFR-1
150 - 200 bar	55M150UFR-2
150 - 200 bar	55M150UFR-3
150 - 200 bar	55M150UFV-1
150 - 200 bar	55M150UFV-2
150 - 200 bar	55M150UFV-3
150 - 200 bar	55M150UFV-4
150 - 200 bar	55M150UFV-5
150 - 200 bar	55M150UFV-6
180 - 200 bar	55M180UFV-1
180 - 200 bar	55M180UFV-2
180 - 200 bar	55M180UFV-3

ENGINEERED UNIT, EVERSAFE IG-100 at 2900 or 4350 psi (200 or 300 bar) IG-100 (Nitrogen) Clean Agent Extinguishing System Units, stored pressure type, having nominal charging capacities as identified below. The units are pressurized to 200 or 300 bar with operating temperatures of -4°F (-20°C) to 122°F (50°C). The units are designed for total-flooding protection against Class A surface burning, Class B flammable liquid, and Class C fires occurring within an enclosure.

A description of these extinguishing system units and the design and installation limitations are contained in the Listee's Installation manual, P/N I.IG-100.Rv.01, Design Manual, P/N D.IG-100.Rv.01, Components Manual P/N C.IG-100.Rv.01 and Maintenance Manual P/N M.IG-100.Rv.01. These installations require the use of the Listee's flow calculation software Nitrogen-Calculation program, Version 7.3. Copies are available from the above Listee.

AGENT STORAGE CONTAINER ASSEMBLY

Nominal Capacity (L)	Part No.
2 - 200 bar	100M2UFV-1
2 - 200 bar	100M2UFV-2
2 - 200 bar	100M2UFV-3
2.7 - 200 bar	100M2UFJ-1
2.7 - 200 bar	100M2UFJ-2

2.7 - 200 bar	100M2UFJ-3
2.7 - 200 bar	100M2UFV-4
2.7 - 200 bar	100M2UFV-5
2.7 - 200 bar	100M2UFV-6
4.7 - 200 bar	100M4UFJ-1
4.7 - 200 bar	100M4UFJ-2
4.7 - 200 bar	100M4UFJ-3
4.7 - 200 bar	100M4UFJ-4
4.7 - 200 bar	100M4UFJ-5
4.7 - 200 bar	100M4UFJ-6
4.7 - 200 bar	100M4UFV-1
4.7 - 200 bar	100M4UFV-2
4.7 - 200 bar	100M4UFV-3
4.7 - 200 bar	100M4UFV-4
4.7 - 200 bar	100M4UFV-5
4.7 - 200 bar	100M4UFV-6
6.7 - 200 bar	100M6UFJ-1
6.7 - 200 bar	100M6UFJ-2
6.7 - 200 bar	100M6UFJ-3
6.7 - 200 bar	100M6UFV-1
6.7 - 200 bar	100M6UFV-2
6.7 - 200 bar	100M6UFV-3
13.4 - 200 bar	100M13UFV-1
13.4 - 200 bar	100M13UFV-2
13.4 - 200 bar	100M13UFV-3
13.4 - 200 bar	100M13UFB-1
13.4 - 200 bar	100M13UFB-2
13.4 - 200 bar	100M13UFB-3
13.4 - 200 bar	100M13UFJ-1
13.4 - 200 bar	100M13UFJ-2
13.4 - 200 bar	100M13UFJ-3
13.4 - 200 bar	100M13UFV-4
13.4 - 200 bar	100M13UFV-5
13.4 - 200 bar	100M13UFV-6

26.8 - 200 bar	100M26UFB-1
26.8 - 200 bar	100M26UFB-2
26.8 - 200 bar	100M26UFB-3
26.8 - 200 bar	100M26UFJ-1
26.8 - 200 bar	100M26UFJ-2
26.8 - 200 bar	100M26UFJ-3
26.8 - 200 bar	100M26UFJ-4
26.8 - 200 bar	100M26UFJ-5
26.8 - 200 bar	100M26UFJ-6
26.8 - 200 bar	100M26UFV-1
26.8 - 200 bar	100M26UFV-2
26.8 - 200 bar	100M26UFV-3
26.8 - 200 bar	100M26UFV-4
26.8 - 200 bar	100M26UFV-5
26.8 - 200 bar	100M26UFV-6
26.8 - 200/300 bar	100M26UFV-7
26.8 - 200/300 bar	100M26UFV-8
26.8 - 200/300 bar	100M26UFV-9
26.8 - 200/300 bar	100M26UFV-10
26.8 - 200/300 bar	100M26UFV-14
26.8 - 200 bar	100M26UFV-11
26.8 - 200 bar	100M26UFV-12
26.8 - 200 bar	100M26UFV-13
40 - 200 bar	100M40UFJ-1
40 - 200 bar	100M40UFJ-2
40 - 200 bar	100M40UFJ-3
40 - 200 bar	100M40UFJ-4
40 - 200 bar	100M40UFJ-5
40 - 200 bar	100M40UFJ-6
40 - 200 bar	100M40UFN-1
40 - 200 bar	100M40UFN-2
40 - 200 bar	100M40UFN-3
40 - 200/300 bar	100M40UFN-4

40 - 200/300 bar	100M40UFN-5
40 - 200/300 bar	100M40UFN-6
40 - 200/300 bar	100M40UFN-7
40 - 200/300 bar	100M40UFN-8
40 - 200 bar	100M40UFV-1
40.2 - 200 bar	100M40UFV-2
40.2 - 200 bar	100M40UFV-3
40.2 - 200 bar	100M40UFV-4
40.2 - 200 bar	100M40UFV-5
40.2 - 200 bar	100M40UFV-6
40.2 - 200/300 bar	100M40UFV-7
40.2 - 200/300 bar	100M40UFV-8
40.2 - 200/300 bar	100M40UFV-9
40.2 - 200/300 bar	100M40UFV-10
40.2 - 200/300 bar	100M40UFV-14
40.2 - 200 bar	100M40UFV-11
40.2 - 200 bar	100M40UFV-12
40.2 - 200 bar	100M40UFV-13
67.5 - 200 bar	100M67UFB-1
67.5 - 200 bar	100M67UFB-2
67.5 - 200 bar	100M67UFB-3
67.5 - 200 bar	100M67UFJ-1
67.5 - 200 bar	100M67UFJ-2
67.5 - 200 bar	100M67UFJ-3
67.5 - 200 bar	100M67UFR-1
67.5 - 200 bar	100M67UFR-2
67.5 - 200 bar	100M67UFR-3
67.5 - 200/300 bar	100M67UFV-1
67.5 - 200/300 bar	100M67UFV-2
67.5 - 200/300 bar	100M67UFV-3
67.5 - 200/300 bar	100M67UFV-4
67.5 - 200/300 bar	100M67UFV-11
68 - 200 bar	100M67UFV-5
68 - 200 bar	100M67UFV-6

68 - 200 bar	100M67UFV-7
67.5 - 200 bar	100M67UFV-8
67.5 - 200 bar	100M67UFV-9
67.5 - 200 bar	100M67UFV-10
80 - 200 bar	100M80UFJ-1
80 - 200 bar	100M80UFJ-2
80 - 200 bar	100M80UFJ-3
80 - 200 bar	100M80UFC-1
80 - 200 bar	100M80UFC-2
80 - 200 bar	100M80UFC-3
80 - 200 bar	100M80UFR-1
80 - 200 bar	100M80UFR-2
80 - 200 bar	100M80UFR-3
80 - 200 bar	100M80UFV-1
80 - 200 bar	100M80UFV-2
80 - 200 bar	100M80UFV-3
80 - 200 bar	100M80UFB-1
80 - 200 bar	100M80UFB-2
80 - 200 bar	100M80UFB-3
80 - 200/300 bar	100M80UFC-4
80 - 200/300 bar	100M80UFC-5
80 - 200/300 bar	100M80UFC-6
80 - 200/300 bar	100M80UFC-7
80 - 200/300 bar	100M80UFC-8
80 - 200/300 bar	100M80UFV-4
80 - 200/300 bar	100M80UFV-5
80 - 200/300 bar	100M80UFV-6
80 - 200/300 bar	100M80UFV-7
80 - 200/300 bar	100M80UFV-11
80 - 200 bar	100M80UFV-8
80 - 200 bar	100M80UFV-9
80 - 200 bar	100M80UFV-10
100 - 200 bar	100M100UFR-1

100 - 200 bar	100M100UFR-2
100 - 200 bar	100M100UFR-3
100 - 200 bar	100M100UFV-1
100 - 200 bar	100M100UFV-2
100 - 200 bar	100M100UFV-3
100 - 200 bar	100M100UFV-4
100 - 200 bar	100M100UFV-5
100 - 200 bar	100M100UFV-6
120 - 200 bar	100M120UFR-1
120 - 200 bar	100M120UFR-2
120 - 200 bar	100M120UFR-3
120 - 200 bar	100M120UFV-1
120 - 200 bar	100M120UFV-2
120 - 200 bar	100M120UFV-3
120 - 200 bar	100M120UFV-4
120 - 200 bar	100M120UFV-5
120 - 200 bar	100M120UFV-6
140 - 200 bar	100M140UFC-1
140 - 200 bar	100M140UFC-2
140 - 200 bar	100M140UFC-3
140 - 200 bar	100M140UFR-1
140 - 200 bar	100M140UFR-2
140 - 200 bar	100M140UFR-3
140 - 200 bar	100M140UFV-1
140 - 200 bar	100M140UFV-2
140 - 200 bar	100M140UFV-3
140 - 200/300 bar	100M140UFC-4
140 - 200/300 bar	100M140UFC-5
140 - 200/300 bar	100M140UFC-6
140 - 200/300 bar	100M140UFC-7
140 - 200/300 bar	100M140UFC-8
140 - 200/300 bar	100M140UFV-4
140 - 200/300 bar	100M140UFV-5
140 - 200/300 bar	100M140UFV-6

140 - 200/300 bar	100M140UFV-7
140 - 200/300 bar	100M140UFV-11
140 - 200 bar	100M140UFV-8
140 - 200 bar	100M140UFV-9
140 - 200 bar	100M140UFV-10
150 - 200 bar	100M150UFR-1
150 - 200 bar	100M150UFR-2
150 - 200 bar	100M150UFR-3
150 - 200 bar	100M150UFV-1
150 - 200 bar	100M150UFV-2
150 - 200 bar	100M150UFV-3
150 - 200 bar	100M150UFV-4
150 - 200 bar	100M150UFV-5
150 - 200 bar	100M150UFV-6
180 - 200 bar	100M180UFV-1
180 - 200 bar	100M180UFV-2
180 - 200 bar	100M180UFV-3

ENGINEERED UNIT, EVERSAFE IG-541 at 2900 or 4350 psi (200 or 300 bar) IG-541 (Ar & N2 & CO2) Clean Agent Extinguishing System Units, stored pressure type, having nominal charging capacities as identified below. The units are pressurized to 200 or 300 bar with operating temperatures of -4°F (-20°C) to 122°F (50°C). The units are designed for total-flooding protection against Class A surface burning, Class B flammable liquid, and Class C fires occurring within an enclosure.

A description of these extinguishing system units and the design and installation limitations are contained in the Listee's Installation manual, P/N I.IG-541.Rv.01, Design Manual, P/N D.IG-541.Rv.01, Components Manual P/N C.IG-541.Rv.01 and Maintenance Manual P/N M.IG-541.Rv.01. These installations require the use of the Listee's flow calculation software IG541-Calculation program, Version 7.3. Copies are available from the above Listee.

AGENT STORAGE CONTAINER ASSEMBLY

Nominal Capacity (L)	Part No.
----------------------	----------

2 - 200 bar	541M2UFV-1
2 - 200 bar	541M2UFV-2
2 - 200 bar	541M2UFV-3
2.7 - 200 bar	541M2UFJ-1

2.7 - 200 bar	541M2UFJ-2
2.7 - 200 bar	541M2UFJ-3
2.7 - 200 bar	541M2UFV-4
2.7 - 200 bar	541M2UFV-5
2.7 - 200 bar	541M2UFV-6
4.7 - 200 bar	541M4UFJ-1
4.7 - 200 bar	541M4UFJ-2
4.7 - 200 bar	541M4UFJ-3
4.7 - 200 bar	541M4UFJ-4
4.7 - 200 bar	541M4UFJ-5
4.7 - 200 bar	541M4UFJ-6
4.7 - 200 bar	541M4UFV-1
4.7 - 200 bar	541M4UFV-2
4.7 - 200 bar	541M4UFV-3
4.7 - 200 bar	541M4UFV-4
4.7 - 200 bar	541M4UFV-5
4.7 - 200 bar	541M4UFV-6
6.7 - 200 bar	541M6UFJ-1
6.7 - 200 bar	541M6UFJ-2
6.7 - 200 bar	541M6UFJ-3
6.7 - 200 bar	541M6UFV-1
6.7 - 200 bar	541M6UFV-2
6.7 - 200 bar	541M6UFV-3
13.4 - 200 bar	541M13UFV-1
13.4 - 200 bar	541M13UFV-2
13.4 - 200 bar	541M13UFV-3
13.4 - 200 bar	541M13UFB-1
13.4 - 200 bar	541M13UFB-2
13.4 - 200 bar	541M13UFB-3
13.4 - 200 bar	541M13UFJ-1
13.4 - 200 bar	541M13UFJ-2
13.4 - 200 bar	541M13UFJ-3
13.4 - 200 bar	541M13UFV-4
13.4 - 200 bar	541M13UFV-5

13.4 - 200 bar	541M13UFV-6
26.8 - 200 bar	541M26UFB-1
26.8 - 200 bar	541M26UFB-2
26.8 - 200 bar	541M26UFB-3
26.8 - 200 bar	541M26UFJ-1
26.8 - 200 bar	541M26UFJ-2
26.8 - 200 bar	541M26UFJ-3
26.8 - 200 bar	541M26UFJ-4
26.8 - 200 bar	541M26UFJ-5
26.8 - 200 bar	541M26UFJ-6
26.8 - 200 bar	541M26UFV-1
26.8 - 200 bar	541M26UFV-2
26.8 - 200 bar	541M26UFV-3
26.8 - 200 bar	541M26UFV-4
26.8 - 200 bar	541M26UFV-5
26.8 - 200 bar	541M26UFV-6
26.8 - 200/300 bar	541M26UFV-7
26.8 - 200/300 bar	541M26UFV-8
26.8 - 200/300 bar	541M26UFV-9
26.8 - 200/300 bar	541M26UFV-10
26.8 - 200/300 bar	541M26UFV-14
26.8 - 200 bar	541M26UFV-11
26.8 - 200 bar	541M26UFV-12
26.8 - 200 bar	541M26UFV-13
40 - 200 bar	541M40UFJ-1
40 - 200 bar	541M40UFJ-2
40 - 200 bar	541M40UFJ-3
40 - 200 bar	541M40UFJ-4
40 - 200 bar	541M40UFJ-5
40 - 200 bar	541M40UFJ-6
40 - 200 bar	541M40UFN-1
40 - 200 bar	541M40UFN-2
40 - 200 bar	541M40UFN-3

40 - 200/300 bar	541M40UFN-4
40 - 200/300 bar	541M40UFN-5
40 - 200/300 bar	541M40UFN-6
40 - 200/300 bar	541M40UFN-7
40 - 200/300 bar	541M40UFN-8
40 - 200 bar	541M40UFV-1
40.2 - 200 bar	541M40UFV-2
40.2 - 200 bar	541M40UFV-3
40.2 - 200 bar	541M40UFV-4
40.2 - 200 bar	541M40UFV-5
40.2 - 200 bar	541M40UFV-6
40.2 - 200/300 bar	541M40UFV-7
40.2 - 200/300 bar	541M40UFV-8
40.2 - 200/300 bar	541M40UFV-9
40.2 - 200/300 bar	541M40UFV-10
40.2 - 200/300 bar	541M40UFV-14
40.2 - 200 bar	541M40UFV-11
40.2 - 200 bar	541M40UFV-12
40.2 - 200 bar	541M40UFV-13
67.5 - 200 bar	541M67UFB-1
67.5 - 200 bar	541M67UFB-2
67.5 - 200 bar	541M67UFB-3
67.5 - 200 bar	541M67UFJ-1
67.5 - 200 bar	541M67UFJ-2
67.5 - 200 bar	541M67UFJ-3
67.5 - 200 bar	541M67UFR-1
67.5 - 200 bar	541M67UFR-2
67.5 - 200 bar	541M67UFR-3
67.5 - 200/300 bar	541M67UFV-1
67.5 - 200/300 bar	541M67UFV-2
67.5 - 200/300 bar	541M67UFV-3
67.5 - 200/300 bar	541M67UFV-4
67.5 - 200/300 bar	541M67UFV-11
68 - 200 bar	541M67UFV-5

68 - 200 bar	541M67UFV-6
68 - 200 bar	541M67UFV-7
67.5 - 200 bar	541M67UFV-8
67.5 - 200 bar	541M67UFV-9
67.5 - 200 bar	541M67UFV-10
80 - 200 bar	541M80UFJ-1
80 - 200 bar	541M80UFJ-2
80 - 200 bar	541M80UFJ-3
80 - 200 bar	541M80UFC-1
80 - 200 bar	541M80UFC-2
80 - 200 bar	541M80UFC-3
80 - 200 bar	541M80UFR-1
80 - 200 bar	541M80UFR-2
80 - 200 bar	541M80UFR-3
80 - 200 bar	541M80UFV-1
80 - 200 bar	541M80UFV-2
80 - 200 bar	541M80UFV-3
80 - 200 bar	541M80UFB-1
80 - 200 bar	541M80UFB-2
80 - 200 bar	541M80UFB-3
80 - 200/300 bar	541M80UFC-4
80 - 200/300 bar	541M80UFC-5
80 - 200/300 bar	541M80UFC-6
80 - 200/300 bar	541M80UFC-7
80 - 200/300 bar	541M80UFC-8
80 - 200/300 bar	541M80UFV-4
80 - 200/300 bar	541M80UFV-5
80 - 200/300 bar	541M80UFV-6
80 - 200/300 bar	541M80UFV-7
80 - 200/300 bar	541M80UFV-11
80 - 200 bar	541M80UFV-8
80 - 200 bar	541M80UFV-9
80 - 200 bar	541M80UFV-10

100 - 200 bar	541M100UFR-1
100 - 200 bar	541M100UFR-2
100 - 200 bar	541M100UFR-3
100 - 200 bar	541M100UFV-1
100 - 200 bar	541M100UFV-2
100 - 200 bar	541M100UFV-3
100 - 200 bar	541M100UFV-4
100 - 200 bar	541M100UFV-5
100 - 200 bar	541M100UFV-6
120 - 200 bar	541M120UFR-1
120 - 200 bar	541M120UFR-2
120 - 200 bar	541M120UFR-3
120 - 200 bar	541M120UFV-1
120 - 200 bar	541M120UFV-2
120 - 200 bar	541M120UFV-3
120 - 200 bar	541M120UFV-4
120 - 200 bar	541M120UFV-5
120 - 200 bar	541M120UFV-6
140 - 200 bar	541M140UFC-1
140 - 200 bar	541M140UFC-2
140 - 200 bar	541M140UFC-3
140 - 200 bar	541M140UFR-1
140 - 200 bar	541M140UFR-2
140 - 200 bar	541M140UFR-3
140 - 200 bar	541M140UFV-1
140 - 200 bar	541M140UFV-2
140 - 200 bar	541M140UFV-3
140 - 200/300 bar	541M140UFC-4
140 - 200/300 bar	541M140UFC-5
140 - 200/300 bar	541M140UFC-6
140 - 200/300 bar	541M140UFC-7
140 - 200/300 bar	541M140UFC-8
140 - 200/300 bar	541M140UFV-4
140 - 200/300 bar	541M140UFV-5

140 - 200/300 bar	541M140UFV-6
140 - 200/300 bar	541M140UFV-7
140 - 200/300 bar	541M140UFV-11
140 - 200 bar	541M140UFV-8
140 - 200 bar	541M140UFV-9
140 - 200 bar	541M140UFV-10
150 - 200 bar	541M150UFR-1
150 - 200 bar	541M150UFR-2
150 - 200 bar	541M150UFR-3
150 - 200 bar	541M150UFV-1
150 - 200 bar	541M150UFV-2
150 - 200 bar	541M150UFV-3
150 - 200 bar	541M150UFV-4
150 - 200 bar	541M150UFV-5
150 - 200 bar	541M150UFV-6
180 - 200 bar	541M180UFV-1
180 - 200 bar	541M180UFV-2
180 - 200 bar	541M180UFV-3

Last Updated on 2016-12-20

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2019 UL LLC".

UL and the UL logo are trademarks of UL LLC © 2019 All Rights Reserved.